

OIML Member State
The Netherlands

Number R21/2007-B-NL1-18.01
Project number 1900283
Page 1 of 2

Issuing authority	NMi Certin B.V. Person responsible: C. Oosterman
Applicant and Manufacturer	Interfacom S.A. Perú, 104 08018 Barcelona Spain
Identification of the certified type	Taximeter Manufacturers mark : Taxitronic Type : TX80
Characteristics	See next page

This OIML Certificate is issued under scheme B.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 21 - Edition 2007

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority **NMi Certin B.V., OIML Issuing Authority NL1**
12 March 2018



C. Oosterman
Head Certification Board

NMi Certin B.V.
Hugo de Grootplein 1
3314 EG Dordrecht
the Netherlands
T +31 78 6332332
certin@nmi.nl
www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org



OIML Member State
The Netherlands

Number R21/2007-B-NL1-18.01
Project number 1900283
Page 2 of 2

The conformity was established by the results of tests and examinations provided in the associated OIML Report:

- No. NMI-1900283-01 dated 29 January 2018 that includes 35 pages.

Characteristics of the taximeter:

Electromagnetic immunity class		E3	
Mechanical environment class		M3	
Climatic environment	temperature range	-25 °C / +70 °C	
	humidity	Condensing	
	intended location	Closed	
		Range	Resolution
Distance signal generator constant k [km ⁻¹]		500 to 80000	1
Time tariff [CU/h]		0,01 to 359964	0,01
Distance tariff [CU/km]		0,01 to 99990	0,01
CU = Currency Unit			
Time measuring signal frequency		10 Hz	
Power supply voltage		10 – 30 V DC	
Software identification		Version number	Checksum
	TX80 box	2.08	9E02
	Skyglass	2.01	E48D