

OIML Member State
The Netherlands

Number R21/2007-B-NL1-19.01
Project number 2224566
Page 1 of 2

Issuing authority NMI Certin B.V.
Person responsible: C. Oosterman

Applicant and Manufacturer Euphoria software BV
Wilhelminapark 36
5041 EC Tilburg
The Netherlands

Identification of the certified type **Taximeter**
Type : Cabman MDT

Characteristics See next page

This OIML Certificate is issued under scheme B.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 21 - Edition 2007

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority **NMI Certin B.V., OIML Issuing Authority NL1**
24 May 2019


C. Oosterman
Head Certification Board

NMI Certin B.V.
Thijsseweg 11
2629 JA Delft
The Netherlands
T +31 88 636 2332
certin@nmi.nl
www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMI Certin B.V. as Issuing Authority can be verified at www.oiml.org



OIML Member State
The Netherlands

Number R21/2007-B-NL1-19.01
Project number 2224566
Page 2 of 2

The conformity was established by the results of tests and examinations provided in the associated OIML Report(s):

- No. NMI-2224566-01 dated 24 May 2019 that includes 42 pages.

Characteristics of the taximeter:

| | | |
|--|--|-----------------|
| Electromagnetic immunity class | E3 | |
| Mechanical environment class | M3 | |
| Climatic environment | temperature range | -20 °C / +70 °C |
| | humidity | condensing |
| | intended location | closed |
| | Range | Resolution |
| Distance signal generator constant k [km ⁻¹] | 500 to 100000 | 1 |
| Time tariff [CU/h] | 0.00 to 3600.00 | 0.01 |
| Distance tariff [CU/km] | 0.00 to 140.00 | 0.01 |
| CU = Currency Unit | | |
| Time measuring signal frequency | 10 Hz | |
| Power supply voltage | 9 - 16 V DC | |
| Software identification | Version number: 0.9-1B9971C0 Checksum: 19CA7CAF | |