

## OIML Certificate of Conformity

**OIML Member State** 

The Netherlands

Number R60/2000-NL1-11.08 Project number 10200905 Page 1 of 2

NMi Certin B.V

Person responsible: C. Ooster

Minebea **Applicant** 

1-1-1, Katase Fujisawa-shi, Kanagawa-ken 251-8531

Japan

Manufacturer Minebea

1-1-1, Katase Fujisawa-shi, Kanagawa-ken 251-8531

Japan

Identification of the

certified type

A bending beam Load Cell

**CB063** 

Characteristics See next page

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R60 - Edition 2000 (E) for accuracy class C

This Certificate relates only to the metrological and technical characteristics of the type of meas instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

NMi Certin B.V.,

2 May 2011

Head Certification Boar

NMi Certin B V Hugo de Grootplein 1 3314 EG Dordrecht the Netherlands T+31 78 6332332 certin@nmi.nl www.nmi.nl

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

Parties concerned can lodge objection against this decision, within six weeks after the date of submission, to the general manager of NMi (see www.nmi.nl).







## OIML Certificate of Conformity

## **OIML Member State**

The Netherlands

Number R60/2000-NL1-11.08 Project number 10200905 Page 2 of 2

The conformity was established by the results of tests and examinations provided in the associated OIML Test Report(s):

- No. NMi-10200905-01 dated 2 May 2011 that includes 60 pages;
- No. NMi-10200905-02 dated 2 May 2011 that includes 54 pages.

## **Characteristics of the Load Cell:**

Fraction P<sub>i</sub> : 0,7

Maximum capacity (E<sub>max</sub>) : 50 kg up to and including 300 kg

Humidity Class : CH

Temperature range :  $-10 \,^{\circ}\text{C} / +40 \,^{\circ}\text{C}$ 

Accuracy Class : C

Maximum number of load cell intervals (n) : 3000 Ratio of minimum LC Verification interval : 10000

 $Y = E_{max} / V_{min}$ 

Ratio of minimum dead load output return : 3000

 $Z = E_{max} / (2 * DR)$