

**OIML Member State** 

The Netherlands

## **OIML** Certificate



Number R60/2017-A-NL1-23.23 revision 2 Project number 3919533 Page 1 of 3

Issuing authority	NMi Certin B.V. Person responsible: M.Ph.D	). Schmidt		
Applicant and Manufacturer	Mettler-Toledo GmbH Im Langacher 44 CH-8606 Greifensee Switzerland			
Identification of the certified type	A <b>single point load cell</b> , Registered trade name	with strain o	gauges, equipped METTLER TOLE	with electronics. DO
	Туре	:	SLP33xD-RTU, S	SLP33xD-IOL (x=1,2,3)
Characteristics	See next page			

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 60-1:2017 for accuracy class C

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

This certificate and supporting reports comply with the requirements of OIML-CS-PD-07 clause 6.2.

*Important note:* Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.

Issuing Authority



NMi Certin B.V. Thijsseweg 11 2629 JA Delft The Netherlands T +31 88 6362332 certin@nmi.nl www.nmi.nl NMi Certin B.V., OIML Issuing Authority NL1 19 June 2025

#### **Certification Board**

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon on top of the electronic version of this certificate.







# **OIML** Certificate

OIML	Member	State
The Ne	etherland	5

Number R60/2017-A-NL1-23.23 revision 2 Project number 3919533 Page 2 of 3

The conformity was established by the results of tests and examinations provided in the associated reports:

- No. NMi-11200209-02 Revision 1 dated 28 April 2014 that includes 49 pages;
- No. NMi-3512445-01 dated 10 August 2023 that includes 63 pages;
- No. NMi-3512445-02 dated 10 August 2023 that includes 46 pages;
- No. NMi-3919533-01 revision 1 dated 19 June 2025 that includes 46 pages.

### Characteristics of the load cell:

Characterization of load cell capabilities		Digital load cell with data processing		
Maximum capacity (E <sub>max</sub> )		5 kg up to and including 1000 kg		
Minimum dead load		0 kg		
Accuracy Class		с		
Maximum number of load cell intervals (n) <sup>(1)</sup>		6000		
Ratio of minimum LC Verification interval <sup>(1)</sup> Y = $E_{max} / v_{min}$		25000		
Ratio of minimum dead load output return <sup>(1)</sup> Z = $E_{max}$ / (2 * DR)		6000		
Fraction p <sub>LC</sub>		0,8		
Humidity Class		СН		
Safe overload		150 % of E <sub>max</sub>		
Recommended excitation		12 - 24 V DC		
Excitation maximum		30 V DC		
Transducer material		Aluminium		
Atmospheric protection		Silicon rubber		
Electromagnetic environment class		E2		
Number of counts for E <sub>max</sub>		≥ Y * 5 / p <sub>LC</sub>		
Software identification		As described in the Mettler-Toledo Rainbow software certificate TC8039		
Data transmission	interface and data protocol	MT-SCIS Level 0_1		
	filtering	adaptive		
	sample frequency	366,21 Hz		

Remark:

1. The characteristics for  $n_{max}$ , Y and Z can be reduced separately.

Each load cell produced is provided with an accompanying document with information about its characteristics.



# **OIML** Certificate



**OIML Member State** The Netherlands Number R60/2017-A-NL1-23.23 revision 2 Project number 3919533 Page 3 of 3

The above identified Type (represented by the sample(s) identified in the OIML Test Report) have been found to comply with the additional national requirements established by the United States of America (NIST Handbook 44 and NCWM Publication 14), included in the Utilizer Declaration:

- R 60 OIML-CS rev.2 Additional requirements from the United States Accuracy class III L;
- R 60 OIML-CS rev.2 Additional requirements from the United States Marking requirements.

### **Revision History**

This revision replaces the previous versions.

Revision	Date	Change(s)
0	2023-08-10	Initial issue.
1	2025-05-19	Upgrading E <sub>max</sub> to 1000 kg.
2	2025-06-19	Correction of type name in test report.



