M	(ΙΜΙ	L Cer	tificate	
OIML Member State The Netherlands			umber 365771	1-24.20 revision 0 1	
Issuing authority	NMi Certin B.V. Person responsible: M.Ph.D. Sc	hmidt			
Applicant and Manufacturer	VPG Precision Transducers Indi OZ-22 Hi-Tech SEZ Kancheepuram 602105 Tamil Nadu India	a Ltd.			
Identification of the certified type	A single point load cell , wit Registered trade name	:	uges. VPG force sens Huntleigh	sors or Tedea-	
	Туре		vLite 0022, vLi vLite 0042	te 0031, vLite 0038 or	
Characteristics	See next page				

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 60-1:2021 for accuracy class C

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Reports is not permitted, although either may be reproduced in full.

Issuing Authority



NMi Certin B.V. Thijsseweg 11 2629 JA Delft The Netherlands T +31 88 6362332 certin@nmi.nl www.nmi.nl NMi Certin B.V., OIML Issuing Authority NL1 11 July 2024

Certification Board

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon on top of the electronic version of this certificate.







OIML Member State

The Netherlands

OIML Certificate



Number R60/2021-A-NL1-24.20 revision 0 Project number 3657711 Page 2 of 3

The conformity was established by the results of tests and examinations provided in the associated reports:

- No. NMi-3657711-02 dated 11 July 2024 that includes 51 pages;
- No. NMi-3657711-03 dated 11 July 2024 that includes 46 pages.

Characteristics of the load cell:

Characterization of load cell capabilities	Analog-passive load cell			
Maximum capacity (E _{max})	50 kg up to and 100 kg100 up to and including 300 kg			
Minimum dead load	0 kg			
Accuracy Class	C			
Rated Output	2 mV/V			
Maximum number of load cell intervals (n) $^{(1)}$	3000			
Ratio of minimum LC Verification interval ⁽¹⁾ Y = E_{max} / v_{min}	12000 15000			
Ratio of minimum dead load output return ⁽¹⁾ Z = E_{max} / (2 * DR)	6000			
Input impedance	410 Ω ± 25 Ω			
Temperature range	-10 °C / +40 °C			
Fraction p_{LC}	0,7			
Humidity Class	СН			
Safe overload	150 % of E _{max}			
Output impedance	354 Ω ± 5 Ω			
Recommended excitation	10 V AC / DC			
Excitation maximum	15 V AC / DC			
Transducer material	(Coated) Aluminium			
Atmospheric protection	Silicone Rubber			

Remarks:

1. The characteristics for $n_{\mbox{\tiny max}}$, Y and Z can be reduced separately.

Each load cell produced is provided with an accompanying document with information about its characteristics.



OIML Certificate



OIML Member State The Netherlands Number R60/2021-A-NL1-24.20 revision 0 Project number 3657711 Page 3 of 3

The above identified Type (represented by the samples identified in the OIML Test Report) have been found to comply with the additional national requirements established by the United States of America (NIST Handbook 44 and NCWM Publication 14), included in the Utilizer Declaration:

- R 60 OIML-CS rev.2 Additional requirements from the United States Marking requirements.
- R 60 OIML-CS rev.2 Additional requirements from the United States Marking requirements.

Revision History

Revision	Date	Change(s)	
0	2024-07-11	Initial issue.	