



certified type

OIML Certificate

OIML Member State The Netherlands



Number R60/2021-A-NL1-24.22 revision 0 Project number 3774623 Page 1 of 3

Issuing authority NMi Certin B.V.

Person responsible: M.Ph.D. Schmidt

Applicant and Ningbo Maken Tech Co., Ltd

Manufacturer No.1-1, Building No.8, VanYang Crowd Innovation Park

Baifeng Sub-district, Beilun District

Ningbo, China

Identification of the A compression load cell, with strain gauges.

Registered trade name Ningbo Maken Tech Co.,Ltd :

Type BTY

Characteristics See next page

This OIML Certificate is issued under scheme A.

This Certificate attests the conformity of the above identified Type (represented by the sample(s) identified in the OIML Test Report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 60-1:2021 for accuracy class C

This Certificate relates only to the metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML International Recommendation above-identified. This Certificate does not bestow any form of legal international approval.

Important note: Apart from the mention of the Certificate's reference number and the name of the OIML Member State in which the Certificate was issued, partial quotation of the Certificate and of the associated OIML Test Report(s) is not permitted, although either may be reproduced in full.



Issuing Authority

NMi Certin B.V., OIML Issuing Authority NL1 15 July 2024



Certification Board

This document is issued under the provision that no liability is accepted and that the applicant shall indemnify third-party liability.

The notification of NMi Certin B.V. as Issuing Authority can be verified at www.oiml.org

This document is digitally signed and sealed. The digital signature can be verified in the blue ribbon on top of the electronic version of this certificate.







NMi Certin B.V. Thiissewea 11 2629 JA Delft The Netherlands T +31 88 6362332 certin@nmi.nl www.nmi.nl





OIML Certificate

OIML Member StateThe Netherlands



Number R60/2021-A-NL1-24.22 revision 0 Project number 3774623 Page 2 of 3

The conformity was established by the results of tests and examinations provided in the associated report:

No. NMi-3774623-01 dated 15 July 2024 that includes 51 pages.

Characteristics of the load cell:

Characterization of load cell capabilities	Analog-passive load cell			
Maximum capacity (E _{max})	10 t up to and including 50 t			
Minimum dead load	0 t			
Accuracy Class	С			
Rated Output	2 mV/V ± 2 %			
Maximum number of load cell intervals (n) (1)	3000			
Ratio of minimum LC Verification interval $^{(1)}$ Y = E_{max} / v_{min}	20000			
Ratio of minimum dead load output return (1) $Z = E_{max} / (2 * DR)$	7500			
Input impedance	775 Ω ± 10 Ω			
Temperature range 👚	-10 °C / +40°C			
Fraction p _{LC}	0,7			
Humidity Class	СН			
Safe overload	150 % of E _{max}			
Output impedance	702 Ω ± 5 Ω			
Recommended excitation	10 V AC / DC			
Excitation maximum	18 V AC / DC			
Transducer material	Stainless steel			
Atmospheric protection	Hermetically welded			

Remarks:

1. The characteristics for n_{max} , Y and Z can be reduced separately.

Each load cell produced is provided with an accompanying document with information about its characteristics.

The above identified Type (represented by the sample(s) identified in the OIML Test Report) have been found to comply with the additional national requirements established by the United States of America (NIST Handbook 44 and NCWM Publication 14), included in the Utilizer Declaration:

- R 60 OIML-CS rev.2 Additional requirements from the United States Accuracy class III L;
- R 60 OIML-CS rev.2 Additional requirements from the United States Marking requirements.





OIML Member State The Netherlands



Number R60/2021-A-NL1-24.22 revision 0 Project number 3774623



Revision History

Revision	Date	Change(s)			
0	2024-07-15	Initial issue.			

Page 3 of 3









