





**OIML Member State** 

Denmark

OIML Certificate No. R76/2006-A-DK2-23.06 Rev. 1

### OIML CERTIFICATE ISSUED UNDER SCHEME A

**OIML Issuing Authority** 

Name: **FORCE Certification A/S** 

Address: Park Allé 345, 2605 Brøndby, Denmark

Person responsible: Per Rafn Crety

**Applicant** 

Name: Nanjing Bonita Scientific Instrument Co., Ltd.

Address: No.13 Paishan Road, Tangshan Industrial Park,

Jiangning District, NanJing, 211132,

China

Manufacturer Nanjing Bonita Scientific Instrument Co., Ltd.

**Identification of the certified type** (the detailed characteristics will be defined in the additional pages)

BNT300A / BNT600A / BNT1200A / BNT3000A / BNT6000A / BNT300B / BNT600B / BNT1200B / BNT3000B / BNT6000B

**Designation of the module** (if applicable)

Non-automatic weighing instrument

This OIML Certificate attests the conformity of the above identified type (represented by the sample(s) identified in the OIML type evaluation report) with the requirements of the following Recommendation of the International Organization of Legal Metrology (OIML):

OIML R 76-1, Edition (year): 2006

For accuracy class (if applicable): II

Page 1 of 3 pages

# OIML Certificate No. R76/2006-A-DK2-23.06 Rev. 1

This OIML Certificate relates only to metrological and technical characteristics of the type of measuring instrument covered by the relevant OIML Recommendation identified above.

This OIML Certificate does not bestow any form of legal international approval.

The conformity was established by the results of tests and examinations provided in the associated OIML reports:

Type examination report: No. 121-22695.10, dated 09 August 2023, that includes 80 pages Type examination report: No. 125-30475.10, dated 19 September 2025, that includes 19 pages

Type evaluation report: No. 121-22695.90.20, dated 01 September 2023, that includes 22 pages Type evaluation report: No. 125-30475.20, dated 19 September 2025, that includes 23 pages

The technical documentation relating to the identified type is contained in documentation file:

121-22695 and 125-30475

#### **OIML Certificate History**

Revision No.		Date		Description of the modification
Initial version	18 Septem	nber 2023		/ III \
Rev. 1	23 Septem	nber 2055	V	Model BNT6000 added.
			V	Gravity function added
			. 7 -	
	1 //	1 1		7

Identification, signature and stamp

The OIML Issuing Authority

FORCE Certification A/S

Date: 23 September 2025

Michael Lang Sørensen

Project Manager

Important note: Apart from the mention of the Certificate's reference number and the name of the

OIML Member State in which the Certificate is issued, partial quotation of the Certificate and of the associated OIML type evaluation report(s) is not permitted,

although either may be reproduced in full.

## **Descriptive annex**

#### **Characteristics**

Type: BNT300A / BNT600A / BNT1200A / BNT3000A / BNT6000A

BNT300B / BNT600B / BNT1200B / BNT3000B / BNT6000B

Accuracy Class:

Weighing ranges: Single-interval

Maximum capacity (Max): 300 g to 6000 g

Minimum capacity (Min): 300g model: 20 x e

600g models: 20 x d

1200g/3000g/6000g models: 50 x e

Maximum number of

verification scale intervals(n): 6000

Verification scale interval (e=): 0.05 g to 1 g

Maximum tare effect: -Max

Operating temperature range:  $+5 \,^{\circ}\text{C} / +40 \,^{\circ}\text{C}$ 

Power supply: 12 VDC using external AC/DC adapter intended for 100-240

VAC, 50/60 Hz

#### **Software**

The approved software version of the indicator is. 1.03

#### **Devices**

- Initial zero setting device (≤ 20% of Max)
- Semi-automatic zero setting device (≤ 4% of Max)
- Semi-automatic subtractive tare device
- Printing device
- Auxiliary indicating device, d=0.1e (models with verification scale interval  $e = 1 \times 10^k$  g only)
- Extended indicating device, d=0.1e (models with verification scale interval  $e \neq 1 \times 10^k$  g)
- Unit toggling device, only g (gram) and ct (metric carat) are allowed.
- Stable equilibrium, Zero and Net indicators.
- Gravity function

#### **Interfaces**

Communication interfaces:

- RS232

The interface does not have to be secured.