

## Capability Annex

### OIML R 49:2013

	Class 1	Class 2
Minimum flow rate (l/h)	2	2
Maximum flow rate (m <sup>3</sup> /h)	14400	14400
Minimum pipe size (mm)	DN3	DN3
Maximum pipe size (mm)	DN3000	DN3000
Water temperature classes	<input checked="" type="checkbox"/> T30 <input checked="" type="checkbox"/> T30/70 <input checked="" type="checkbox"/> T50 <input checked="" type="checkbox"/> T30/90 <input checked="" type="checkbox"/> T70 <input type="checkbox"/> T30/130 <input checked="" type="checkbox"/> T90 <input type="checkbox"/> T30/180 <input type="checkbox"/> T130 <input type="checkbox"/> T180	<input checked="" type="checkbox"/> T30 <input checked="" type="checkbox"/> T30/70 <input checked="" type="checkbox"/> T50 <input checked="" type="checkbox"/> T30/90 <input checked="" type="checkbox"/> T70 <input type="checkbox"/> T30/130 <input checked="" type="checkbox"/> T90 <input type="checkbox"/> T30/180 <input type="checkbox"/> T130 <input type="checkbox"/> T180
Environmental tests (climatic, electromagnetic compatibility, magnetic field, etc.)	Full range according to OIML R 49:2013	

Restrictions:

or T70, T90, T30/70, T30/90 - Maximum flow rate (m<sup>3</sup>/h) - 4 245 m<sup>3</sup>/h, DN 1100